

# Oilmaster® Composite Hose Type 804

### **Applications**

This type is designed for use as a tank truck, rail car and in-plant transfer hose suitable for use with most petroleum products including unleaded gasoline and 100% aromatics. It is also recommended for bottom loading service as a replacement for conventional metallic drop tubes. A stainless steel outer wire is available for applications which include a corrosive environment.



### **Technical description**

Lining : Polypropylene Inner Wire : Galvanized Steel

Outer Wire : GGP804 Galvanized Steel

GSP804 Stainless Steel 304 or 316

Cover : PVC coated Nylon, Abrasion, UV and ozone resistant, Blue

Temperature range :  $-30^{\circ}$ C to  $+80^{\circ}$ C ( $-22^{\circ}$ F to  $+176^{\circ}$ F)

Electrical properties : Electrically conductive Standard : EN13765:2018, Type 2

Complies with : IMO IBC Code

Approval : ClassNK Certificate N0. TA21511E(AL)

# **Physical properties**

Maximum elongation : 10% on test pressure

Vacuum range : 0,9 bar

#### **End Fittings**

Specially designed end fittings have been developed for use with Amniflex Composite hoses, including threaded ends, flanged ends and other connections. By means of a hydraulic operated press, a ferrule is externally swaged onto the hose to secure the hose shank and guarantee a leak proof connection between hose and fitting. All ferrules are welded to the end fitting before swaging for even safer operating conditions.

Technical data: Type GGP804/GSP804									
		Working		Min. Bend					
Inside Diameter		Pressure		Radius		Approx. Weight		Max. length	
inches	mm	psi	bar	inches	mm	lbs/ft	kg/m	ft.	m
1	25	150	10	4	100	0,65	1,00	65	20
11/2	40	150	10	5¼	130	0,85	1,25	65	20
2	50	150	10	61/2	165	1,20	1,80	65	20
21/2	65	150	10	71/2	185	1,70	2,50	65	20
3	80	150	10	9 ½	240	2,00	3,00	65	20
4	100	150	10	14 ½	360	3,00	4,50	65	20

Safety factor acc. EN 13765:2018

All information in this document is without any obligation, specifications subject to change without any notice.

Amniflex B.V. Abraham van Stolkweg 118 3041 JA, Rotterdam T: +31(0)10 2982121

E: amniflex@plastiflex.com www.amniflex.com BTW nr. NL862140729B01 Bank: KBC Bank NV KREDNL2XXXX

IBAN NL23 KRED0633024376

K.v.K. Rotterdam nr. 81568053



