AMNIFLEX

Chemiflex® Composite Hose Type 436

Applications

This type is recommended for multi chemical transfer service in heavy duty marine operations where economy and maximum chemical resistance of a polypropylene coated inner wire is desired. It is suitable for use as a dock, barge, and ship transfer hose and is available with a stainless steel outer wire for applications which include a corrosive environment.



Technical description

Lining	: Polypropylene
Inner Wire	: Polypropylene Coated Steel
Outer Wire	: PGP436 Galvanized Steel
	PSP436 Stainless Steel 304 or 316
Cover	: PVC coated Nylon, Abrasion, UV and ozone resistant, Black
Temperature range	: -30°C to + 80°C (-22°F to + 176°F)
Electrical properties	: Electrically conductive
Standard	: EN13765:2010, Type 3
Complies with	: IMO IBC code
Approval	: ClassNK Certificate N0. TA21511E(AL)

Physical properties

Maximum elongation	: 10% on test pressure
Vacuum range	: 0,9 bar

End Fittings

Specially designed end fittings have been developed for use with Amniflex Composite hoses, including threaded ends, flanged ends and other connections. By means of a hydraulic operated press, a ferrule is externally swaged onto the hose to secure the hose shank and guarantee a leak proof connection between hose and fitting. All ferrules are welded to the end fitting before swaging for even safer operating conditions.

Technical data: Type PGP436/PSP436											
Inside Diar	neter	Working Pressure		Min. Bend Radius		Approx. Weight		Max. length			
inches	mm	psi	Bar	inches	mm	lbs/ft	kg/m	ft.	m		
3	80	200	14	11	280	2,50	3,70	65	20		
4	100	200	14	16	400	4,40	6,50	65	20		
5	125	200	14	18	460	5,80	8,60	65	20		
6	150	200	14	20	500	7,00	10,50	65	24		
8	200	200	14	29	740	12,00	18,00	65	20		
10	250	150	10	36	920	15,00	23,00	50	15		

*10"= Type 2 Safety factor acc. EN 13765:2018

All information in this document is without any obligation, specifications subject to change without any notice.

Amniflex B.V. Abraham van Stolkweg 118 3041 JA, Rotterdam T: +31(0)10 2982121 E: amniflex@plastiflex.com www.amniflex.com

BTW nr. NL862140729B01 Bank: KBC Bank NV KREDNL2XXXX IBAN NL23 KRED0633024376 K.v.K. Rotterdam nr. 81568053

Al onze aanbiedingen en leveranties geschieden volgens onze algemene leveringsvoorwaarden.

