

Chemiflex® Composite Hose Type 425

Applications

This type is specially constructed with a PTFE lining to handle selected liquid chemicals and acids which are not compatible with polypropylene hoses. It is suitable for tank truck, railcar and in-plant service. A stainless steel outer wire is available for applications which include a corrosive environment.



Technical description

Lining : PTFE

Inner Wire : Stainless Steel 316
Outer Wire : SGF425 Galvanized Steel

SSF425 Stainless Steel 304 or 316

Cover : PVC coated Nylon, Abrasion, UV and ozone resistant, Red

Temperature range : -30°C to + 100°C (-22°F to + 212°F)

Electrical properties : Electrically conductive Standard : EN13765:2018, Type 3

Complies with : IMO IBC code

Approval : ClassNK Certificate N0. TA21511E(AL)

Physical properties

Maximum elongation : 10% on test pressure

Vacuum range : 0,9 bar

End Fittings

Specially designed end fittings have been developed for use with Amniflex Composite hoses, including threaded ends, flanged ends and other connections. By means of a hydraulic operated press, a ferrule is externally swaged onto the hose to secure the hose shank and guarantee a leak proof connection between hose and fitting. All ferrules are welded to the end fitting before swaging for even safer operating conditions.

Technical data: Type SGF425/SSF425									
Inside Diameter		Working Pressure		Min. Bend Radius		Approx. Weight		Max. length	
inches	mm	psi	Bar	inches	mm	lbs/ft	kg/m	ft.	m
1	25	200	14	4	100	0,80	1,10	65	20
1 ½	40	200	14	5 1/4	130	0,95	1,40	65	20
2	50	200	14	6 ½	165	1,35	2,00	65	20
2 ½	65	200	14	7 ½	185	1,80	2,70	65	20
3	80	200	14	9 ½	240	2,15	3,20	65	20
4	100	200	14	14 ½	360	3,25	4,80	65	20

Safety factor acc. EN 13765:2018

All information in this document is without any obligation, specifications subject to change without any notice.

Amniflex B.V. Abraham van Stolkweg 118 3041 JA, Rotterdam T: +31(0)10 2982121

E: amniflex@plastiflex.com

www.amniflex.com

BTW nr. NL862140729B01 Bank: KBC Bank NV KREDNL2XXXX

KREDNL2XXXX Al onze aanbiedingen en leveranties geschieden IBAN NL23 KRED0633024376 volgens onze algemene leveringsvoorwaarden.

